## LA-UR-11-10994

Approved for public release; distribution is unlimited.

Title: Catalyzed Conversion of Non-Food Biomass Using Algal Lipids and

Carbohydrates.

Author(s): Silks, Louis A

Intended for: DOE

First International Conference on Algal Biomass, Biofuels, and Bioproducts, 2011-07-17/2011-07-20 (St. Louis, Missouri, United

States) Poster

Biological resources Reading Room

**RCRA** 



## Disclaimer:

Los Alamos National Laboratory, an affirmative action/equal opportunity employer,is operated by the Los Alamos National Security, LLC for the National NuclearSecurity Administration of the U.S. Department of Energy under contract DE-AC52-06NA25396. By acceptance of this article, the publisher recognizes that the U.S. Government retains nonexclusive, royalty-free license to publish or reproduce the published form of this contribution, or to allow others to do so, for U.S. Government purposes. Los Alamos National Laboratory requests that the publisher identify this article as work performed under the auspices of the U.S. Departmentof Energy. Los Alamos National Laboratory strongly supports academic freedom and a researcher's right to publish; as an institution, however, the Laboratory does not endorse the viewpoint of a publication or guarantee its technical correctness.



## Catalyzed Conversion of Non-Food Biomass Using Algal Lipids and Carbohydrates.

L.A. "Pete" Silks, Ruilian Wu, Jin Kim, John C. Gordon, Ryszard Michalczyk, Cliff J. Unkefer. Los Alamos National Laboratory, Bioscience and Chemistry Divisions, and the National Stable Isotope Resource (B8), MS E529, Los Alamos, New Mexico, 87545, USA.

Biomass, if efficiently converted to high energy density fuel, has the potential to become a sustainable source of this commodity, instead of petroleum. Examples of useful biomass include corn stover, switch grass, wood chips, and grass clippings. Efficient conversion of biomass into fuel could account for 100% of US petroleum imports. This poster will describe our efforts in the conversion of algal products to fuel and useful higher value commodities and the use of catalysis for the conversion of biomass

In order for biomass to become a viable fuel source, an efficient process for its conversion into hydrocarbons (i.e. fuel) must be developed. This conversion process has four steps. First, the cellulosic sugars must be extracted from the biomass source. Next, the carbohydrates undergo a carbon chain extension reaction. The cellulosic starting materials are either five or six carbons in length whereas high-energy density fuels are eight to fifteen carbons in length. This carbon chain extension reaction makes the polyols the proper length for a fuel. This step is often done using an aldol condensation reaction. Finally, the aldol products are deoxygenated and then hydrogenated in order to yield a hydrocarbon that can be burned as a high-energy density fuel.

Algal biomass is attractive since one of it's major sources of carbon is from carbon dioxide and many species are tolerant of brackish environments. This poster will describe our efforts to take algal lipids and converting those to deoxygenated hydrocarbons. In addition, the algal carbohydrates are also attractive for conversion to furan based molecules which are used in fuel production.



## PARTICIPANTS/PARTNERS:

Los Alamos National Laboratory (LANL)
Pacific Northwest National Laboratory (I
University of Arizona (UA) 



National Advanced Biofuels Consortium

Consortium Leads National Renewable Energy Laboratory Pacific Northwest National Laboratory

Pall Corporation RTI International Tesoro Companies Inc. University of California, Davis UOP, LLC Virent Energy Systems Washington State University

## LANL Biomass to Fuels Capabilities



Figure 2. Process for converting biomass into high energy density fuel. This project focused on the carbon chain extension step of this process.

# Non-hood based sources agricultural residues (e.g. on shore), dedicated energy crops, wood residues (e.g. a paper mil discards), munipiel paper waste Using Organocatalyisis: carbon chain extensions to give C9 and C15 Carbon Chains (LANL LDRD)

## Potential Fuel precursors


Table 1.

Catalyst	Yield
Piperidine	61% ( <u>2</u> )
1-methylpiperizine	70% ( <u>1</u> ) + 30% ( <u>2</u> )
(S)-2-Hydroxymethyl piperizine	53% ( <u>2</u> )
(R)-2-Hydroxymethyl piperizine	46% ( <u>2</u> )

2 
$$\longrightarrow$$
 0 Ne'  $\longrightarrow$  0 Ne' 0 Ne'  $\longrightarrow$  0 N


Yields have been good to excellent. Olefins do not appear to affect reaction course. Next steps will be to examine methods for direct conversion of triglycerides to hydrocarbons.

## Direct Conversion of Algal Starch to Higher Value Products (NAABB)



Process uses lanthanides triflates and halides in water Microwave promoted. Currently evaluating conversion precentages

## Synthesis of Site Specifically Stable Isotope Labeled (2H and/or Oligosaccharides for Mechanistic Pyrolysis Studies (NABC)



### **Model Reactions**

Heterolytic cleavage of neutral cellobiose



· Heterolytic cleavage of positively charged



Goal: Understanding pyrolysis mechanisms could give rise to Optimized conversion condictions.

It is believed that biomass can be converted to transportation fuels through carbon chain addition. It is proven that through aldol reactions of biomass these carbon additions are possible. Further tests are needed to show that hydrodeoxygenation can be accomplished under economical conditions.

Biomass derived from algal has been demonstrated to be converted to low oxygen content high energy density hydrocarbons. Current efforts to determine the cost of inputs in the Kolbe reaction will determine if this is an economical viable pathway to these fuels.

Stable isotope labels will be usedful in sorting out the chemiical / processes/steps in pyrolysis of lignocellulosic materials.

We thank the DOE EERE NAABB & NABC and LANL for LDRD DR and ER support for this work.